



## EZ-Pour

### EZ-Pour

#### Applications:

- Residential/Commercial/Institutional/  
Infra-structural Concrete Formwork

#### Surface Characteristics:

- Consistent and smooth face for  
outstanding pours

#### Inner Ply Characteristics:

- Western Species D Grade

#### Outer Ply Characteristics:

- Douglas-fir, "C" Plugged face "D"  
grade back

#### Available:

- 23/32 5 ply only, 4x8, 2x8

FORM

**APA**  
THE ENGINEERED  
WOOD ASSOCIATION

C-D PLUGGED  
BASE PANEL  
23/32 INCH  
GROUP 2  
SIZED FOR SPACING  
EXPOSURE 1

519  
PS1-07



Swanson offers EZ-Pour overlay concrete form to allow project designers and contractors to specify a quality, yet economical, overlay panel for conditions or situations where premium TruPour MDO Plyform's higher performance is not necessary or desired. EZ-Pour is produced with the same Swanson attention to detail and quality control, but uses a lower grade veneer substrate. There is some slight telegraphing of repair to the base-veneer when laminating the overlay to the face.

EZ-Pour MDO Plyform, like our other Plyform panels, has high performance, low maintenance and cost-effectiveness of multiple pours. EZ-Pour MDO is factory sealed with a distinctive blue edge sealer (not paint) specifically designed for exposure to fluid concrete. This unique formulation has exceptional water, alkalis, and sunlight resistance, which ensures maximum panel edge durability where typical panels most often fail. EZ-Pour MDO is treated with the industry leading Nox-Crete Form Coating 250 release agent. EZ-Pour MDO can provide reliable results in multiple pouring cycles when given the proper care, application and treatment during on-site use.





1-800-331-0831

The Swanson Edge.

## Concrete Form SPECIFICATION SHEET

PRODUCT NAME	TruPour HDO FORM 120/30	TruPour HDO FORM 100/30	TruPour MDO	EZ-Pour
Product Description	TruPour HDO Form 120 combines (2) high density laminates with (1) medium density laminate to provide the best forming surface available.	TruPour HDO Form 100 combines (1) High density laminate with (1) medium density laminate for excellent cost to pour ratios.	TruPour MDO is the workhorse of Swanson's concrete form family, producing consistent, smooth surfaces.	EZ-Pour is an option for concrete applications where smooth surfaces are desired, yet economy is a major factor.
Concrete Finish	Architectural	Superior	Excellent	Good
Pour Range	50 to 200	30 to 50	Up to 20	Up to 10
Face Veneer	"B" Grade Douglas-fir	"B" Grade Douglas-fir	"B" Grade Douglas-fir	Repaired "C" Grade Doug-fir
Back Veneer	"C" Grade Douglas-fir	"C" Grade Douglas-fir	"C" Grade Douglas-fir	"D" Grade Douglas-fir
Inner Plies	"C" Grade Douglas-fir	"C" Grade Douglas-fir	"C" Grade Douglas-fir	"D" Grade Western Species
Edge Seal	Nox-Crete Edge Flex 235	Nox-Crete Edge Flex 235	Nox-Crete Edge Flex 235	Nox-Crete Edge Flex 235
Release Agent	Job Site Application	Job Site Application	Nox-Crete Form Coating 250	Nox-Crete Form Coating 250
Available	4' x 8', 2' width, 2-step, Struct-I	4' x 8', 2' width, 2-step, Struct-I	4' x 8', 2' width, 1-sided & 2-sided	4' x 8', 2' width, 1-sided 1-step



PO Box 1779 • Grants Pass, OR 97528

Phone 541-956-4300

1-800-331-0831

Fax 541-956-4289